



GMS15KS-AU
17kVA Standby
13.5kW
15kVA Prime
12kW
Either 240v
Or 415v

Technical

Model	415v	GMS15KS-AU
	240v	PK15S-AU
Type		Heavy duty
Speed		1500RPM
Phase/Voltage		3-415
		1-240
Frequency		50Hz
Standby Power		17kVA
Prime Power		15kVA
Noise Level Av (dba @ 7m)		55dbA
Fuel Capacity		100 L

Alternator

Manufacturer	Stamford
Model	PI144E
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Dimensions & Weight

Length	1.93m
Width	0.90m
Height	1.30m
Weight Dry	770Kg

240v set Outlets

Fitted—BUS connection point
44 x 15a single phase c/w ELCB

415v set Outlets

Fitted—BUS connection point
3 x 15a single phase c/w ELCB
1 x 20a 5 pin 3 phase

Engine

Manufacturer	Kubota
Model	D1703-BG
Type	4 Stroke Diesel
Induction	Naturally Aspired
Fuel Consumption	2.3 L/hr @ 100% Load
Coolant Capacity	5.0L
Governor	Mechanical
Cubic Capacity	1.2 L
Oil Capacity	5.1 L

Controls

Controller	DSE Remote Auto Start
Circuit Breaker	RCD MCBO
Battery Isolator	Fitted
Battery Charger	Fitted

Canopy

Skid	Bunded fuel tank with tie down points and fork lift pockets
Canopy	Centre lift with lockable doors, Galvanized sheet, IP56* External Emergency Stop fitted.
Paint Finish	Heavy Duty Powder Coat White with Black base

Options

PMG Coolant Heater
Installation Service