

GMS10KS-AU 10kVA 3PHASE



Dependable Power

Kubota Diesel 

Stamford Alternator 

Deep Sea Control 

Technical

Model	GMS10KS-AU
Type	Heavy Duty
Speed	1500RPM
Phase/Voltage	3-240/415
Frequency	50Hz
Standby Power	11kVA
Prime Power	10kVA
Noise Level (dba @ 7m)	55dba
Fuel Capacity	100 L
Ambient Temp	50 deg C

Alternator

Manufacturer	Stamford
Model	PIO44G
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Dimensions & Weight

Length	1.99m
Width	0.95m
Height	1.36m
Weight Dry	932Kg

Outlets Optional

Outlets 3 phase	20amp IP66 with RCD CB
Outlets 1 phase	3 x 15amp IP66 with RCD MCBO

Engine

Manufacturer	Kubota
Model	D1703-BG
Type	4 Stroke Diesel
Induction	Naturally Aspired
Fuel Consumption	2.3 L/hr @ 100% Load
Coolant Capacity	5.0L
Governor	Mechanical
Cubic Capacity	1.64 L
Oil Capacity	7.6 L

Controls

Controller	Deep Sea 702 or PLC920
Circuit Breaker	Four Pole RCD MCBO
Battery Isolator	Fitted Lockable
Auto Start	2 wire remote

Canopy

Skid	Bunded fuel tank with tie down points and fork lift pockets
Canopy	Centre lift with lockable doors, Galvanized sheet, IP56* External Emergency Stop fitted.
Paint Finish	Heavy Duty Powder Coat White with Black base

Options

PMG (Battery Charger standard)	Block Heater	Auto Start
--------------------------------	--------------	------------

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.