

GMS15KS-AU 15kVA 3PHASE



Dependable Power

Kubota Diesel 

Stamford Alternator 

Deep Sea Control 

Technical

Model	AG15KS-AU
Type	Heavy duty
Speed	1500RPM
Phase/Voltage	3-240/415
Frequency	50Hz
Standby Power	16.5kVA
Prime Power	15kVA
Noise Level (dba @ 7m)	55dba
Fuel Capacity	100 L

Engine

Manufacturer	Kubota
Model	D1703-BG
Type	4 Stroke Diesel
Induction	Naturally Aspired
Fuel Consumption	2.8 L @ 100% Load
Coolant Capacity	5.0L
Governor	Mechanical
Cubic Capacity	1.67 L
Oil Capacity	7.1 L

Alternator

Manufacturer	Stamford
Model	PI144E
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Controls

Controller	Deep Sea 702 or PLC920
Circuit Breaker	Four Pole RCD MCBO
Battery Isolator	Fitted adjacent to the battery, Lockable
Temperature	50°C Radiator Fitted

Dimensions & Weight

Length	1.93m
Width	0.90m
Height	1.3m
Weight Dry	770Kg

Canopy

Skid	Bunded fuel tank with tie down points and fork lift pockets
Canopy	Centre lift with lockable doors, Galvanized sheet, External Emergency Stop fitted.
Paint Finish	Heavy Duty Powder Coat White with Black base

Outlets

Outlets 3 phase	20amp IP66 with CB
Outlets 1 phase	3 x 15amp IP66 with RCD MCBO

Options

PMG Battery Charger	Block Heater	Auto Start
Installation	Service	

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.