



LIGHTING TOWER

A Good Partner for Illumination!



ALT9000M

NOISE LEVEL: 62dBA@7m



www.ausgen.net.au



Call for a quote today
1300 AUSGEN
2-8-7-4-3-6

Lighting Tower ALT9000M



Stable Performance and Safety


The superior performance of the generator set ensures stable and reliable lighting. The lighting tower is equipped with audible warning system, which will be activated when the mast is being risen or lowered so as to make the operators and people nearby noted and keep in safety distance.

Energy-efficient Metal Halide Lamps

Metal halide lamp can provide enough brightness with little energy, which is one of the most efficient ways to convert electrical energy into light. Compared with other lamps, their light is closer to natural light featuring by longer service life, compact structure and lower energy consumption, it is widely used in various industries.

Compact Structure for High Efficiency

ALT9000M lighting tower mainly consists of a generator set, a telescopic mast, a lighting kit and a trailer. The generator set is featured by large access door for convenient maintenance and large fuel tank for long time work. The telescopic mast can reach 9.012 meters' height at maximum with strong wind resistant performance, and can rotate 350 degree, allowing illumination in all directions. And the trailer makes the machine easy to move. The machine is designed compact and easy to use and to store. It can meet requirements of various applications.



Genset Parameter



Ambient Temperature	50°C
Fast Output Power	2x15 Amp, 230V
Max Height (unfolded)	9012mm
Number of Mast Sections	9
Mast Rising Time	15s
Mast Lowering Time	18s
Rotating Angle of Mast	0~350° (manual)
Pitch Angle of Light Fixture	0~82° (automatic)
Lamp	Metal Halide Lamp, 4x1000W, 220V
Illuminating Power (luminous flux)	85,000 Lumen/ Lamp
Max.Travel Speed	80 km / h
Dimensions (folded)	2414 × 1634 × 2310(mm)
Dimensions (unfolded)	2782 × 2775 × 9012(mm)
Dry Weight	1172kg

Diesel Engine

Model	403D-11G
No. of Cylinders; Diameter x Stroke	3 ; 77 x 81mm
Prime Power	8.6kW
Displacement	1.13L
Fuel Tank	85L
Fuel Consumption (full load)	2.6L/H
Oil Capacity	4.9L

Alternator

Model	LSA40VS1
Excitation	Brushless
Excitation System	Self-exciting
Poles	4
Protection Class	IP23
Insulation Class	H



AUSGEN reserves the right to make changes in model , technical specification,color,equipment and accessories without prior notice.

Lighting Tower ALT9000M / Sep. 2012, Edition 6220037



Call for a quote today
1300 AUSGEN
 2-8-7-4-3-6