



PK10S-AU
11kVA Standby
9kW
10kVA Prime
8kW
240v

Technical

Model	240v	PK10S-AU
Type		Heavy duty
Speed		1500RPM
Phase/Voltage		3-415
		1-240
Frequency		50Hz
Standby Power		11kVA
Prime Power		10kVA
Noise Level Av (dba @ 7m)		55dbA
Fuel Capacity		100 L
Ambient Temp		50deg C

Alternator

Manufacturer		Stamford
Model		PI044H
Type		Brushless
Harmonic Distortion		Less than 5%
Protection Class		IP 23
Insulation Class		Class H

Dimensions & Weight

Length		1.9m
Width		0.90m
Height		1.25m
Weight Dry		652Kg

240v set Outlets

Fitted—BUS connection point
4 x 15a single phase c/w ELCB

Engine

Manufacturer		Kubota
Model		D1105-BG
Type		4 Stroke Diesel
Induction		Naturally Aspired
Fuel Consumption		2.3 L/hr @ 100% Load
Coolant Capacity		5.0L
Governor		Mechanical
Cubic Capacity		1.2 L
Oil Capacity		5.1 L

Controls

Controller		DSE Remote Auto Start
Circuit Breaker		RCD MCBO
Battery Isolator		Fitted
Battery Charger		Fitted

Canopy

Skid		Bunded fuel tank with tie down points and fork lift pockets
Canopy		Centre lift with lockable doors, Galvanized sheet, IP56* External Emergency Stop fitted.
Paint Finish		Heavy Duty Powder Coat White with Black base

Options

PMG Coolant Heater
Installation Service